




Mounting hardware to be ordered separately.

DIMENSIONS

RATED CAPACITY	C	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	H	H1	H2	H3	H4	H5	H6	H7	H8	L	W	W1	T
Klb/inches																									
LE50; 56	1.46	1.57	5.91	2.95	1.61	0.38	2.46	3.75	2.46	4.13	1.57	5.91	7.56	2.87	1.00	2.34	3.78	8.18	1.25	1.69	9.56	2.88	4.13	2.03	M10X1 Depth 15
kN/inches																									
250	1.46	1.57	5.91	2.95	1.61	0.38	2.46	3.75	2.46	4.13	1.57	5.91	7.56	2.87	1.00	2.34	3.78	8.18	1.25	1.69	9.56	2.88	4.13	2.03	M10X1 Depth 15
t/mm (conversion of above dimensions)																									
LE22.7; 25.4; 25.5	37.1	40.0	150.1	75.0	41.0	9.7	62.5	95.3	62.5	104.9	40.0	150.1	192.0	73.0	25.4	59.5	96.0	207.8	31.8	42.9	242.7	73.1	105.0	51.5	M10X1 Depth 15

SPECIFICATIONS

Full Scale Output	LE50Klb: 1.8 mV/V $\pm$ 0.1% 250kN & 56Klb: 2.0 mV/V $\pm$ 0.1%	Recommended Excitation	10V (15V Maximum)
Zero Balance	$\pm$ 0.02 mV/V	Insulation Resistance	>2 [50V DC] G Ω
Non-linearity	$\leq$ $\pm$ 0.030%	Compensated Temperature Range	-10°C to 50°C / 14°F to 122°F
Repeatability	$\leq$ $\pm$ 0.010%	Safe Overload	150% of full scale
Hysteresis Error	$\leq$ $\pm$ 0.020%	Breaking Overload	300% of full scale
Creep in 30 min.	$\leq$ $\pm$ 0.020%	Seal Type / IP Rating	Welded Seal / IP68
Input Resistance	1080 Ω $\pm$ 10	Cable Color Code	Exc+ Red Exc- Black Sig+ Green Sig- White Shield Bare
Output Resistance	1000 Ω $\pm$ 5		
Element Material	2Cr13 Stainless Steel		

PART NUMBER*

Rated Capacity	Part No.	Weight Approx. (kg)
LE50Klb	106RS-FB-LE50Klb-YZ.....	3.5
250kN.....	106RS-FB-250kN-YZ.....	3.5
56Klb.....	106RS-FB20-56Klb-YZ.....	3.5

Mounting Hardware

Mounting Hardware	Part No.	Weight Approx. (kg)
Mounting Cap.....	MC106RS-FB-A1.....	1.1
Mounting Base	MB106RS-FB-A1.....	1.9

* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.



NTEP 1:10 000 Class IIIL, Multiple Cell



OIML MAA C3, Y=16 000

For further available P/N's & specifications per NTEP/OIML classes, please contact us.

INTERCHANGEABLE REFERENCE

Brand	Model
106RS-FB-LE50Klb-YZ	
Coti Global.....	CG-26S1 50K le
Fairbanks.....	LCFHR4020-2, Part# 64166
Rice Lake.....	RL75114

106RS-FB20-56Klb-YZ

Coti Global.....	CG-26S2 56K
Fairbanks.....	LCFHR4020-19
Flintec.....	RC1

Product Datasheet Disclaimer

Information Changes:

All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

 **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.