




Stainless Steel



SINGLE ENDED BEAMS



RATED CAPACITY	C1	C2	H	L	L1	L2	L3	L4	W	T
lb/inches										
500-4,000; SE5,000	0.53	0.53	1.22	5.12	2.25	3.00	1.00	0.62	1.22	1/2-20 UNF-2B
5,000-10,000	0.79	0.79	1.50	6.75	3.00	3.75	1.50	0.75	1.50	3/4-16 UNF-2B
15,000-20,000	1.03	1.03	2.00	8.75	4.00	4.75	2.00	1.00	2.00	1-14 UNS-2B
kg/mm										
250-2,000	13.5	13.5	31.0	130.0	57.2	76.2	25.4	15.8	31.0	M12X1.75
3,000-5,000	20.0	20.0	38.1	171.5	76.2	95.3	38.1	19.1	38.1	M18X1.50
10,000	26.2	26.2	50.8	222.3	101.6	120.7	50.8	25.4	50.8	M24X2.00

SPECIFICATIONS			
Full Scale Output	563YS: 2.0 mV/V ± 0.25%; 563YS30: 3.0 mV/V ± 0.25%		Recommended Excitation
Zero Balance	± 0.02 mV/V		Insulation Resistance
Non-linearity	< ± 0.023%		Compensated Temperature Range
Repeatability	< ± 0.023%		Safe Overload
Hysteresis Error	< ± 0.023%		Breaking Overload
Creep in 30 min.	< ± 0.030%		Seal Type / IP Rating
Input Resistance	350 Ω ± 7		Cable Color Code
Output Resistance	350 Ω ± 3		
Element Material	17-4PH Stainless Steel		

PART NUMBER*			
Rated Capacity	Part No. 2.0 mV/V	Part No. 3.0 mV/V	Weight Approx. (kg)
500lb.....	563YS-500lb	563YS30GS-500lb	1.0
1Klb.....	563YS-1Klb	563YS30-1Klb	1.0
2Klb.....	563YS-2Klb	563YS30-2Klb	1.0
2.5Klb.....	563YS-2.5Klb	563YS30-2.5Klb	1.0
4Klb.....	563YS-4Klb	563YS30-4Klb	1.0
SE5Klb.....	563YS-SE5Klb	563YS30-SE5Klb	1.0
5Klb.....	563YS-5Klb	563YS30-5Klb	1.8
10Klb.....	563YS-10Klb	563YS30-10Klb	1.8
15Klb.....	563YS-15Klb	563YS30-15Klb	4.1
20Klb.....	563YS-20Klb	563YS30-20Klb	4.1
250kg.....	563YS-250kg	-	1.0
500kg.....	563YS-500kg	-	1.0
1t.....	563YS-1t	-	1.0
2t.....	563YS-2t	-	1.0
3t.....	563YS-3t	-	1.8

- Environmentally sealed for 563YS30, capacity=500lb
 - SE refers to small envelope
 * ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

PART NUMBER*			
Rated Capacity	Part No. 2.0 mV/V	Part No. 3.0 mV/V	Weight Approx. (kg)
5t.....	563YS-5t	-	1.8
10t.....	563YS-10t	-	4.1

WEIGH MODULE	
Model	Page
563YSM3-02.....	174
563YS, 500lb-2.5Klb & 250kg-1t: NTEP 1:5 000 Class III, S; NTEP 1:9 500 Class III, M 4Klb-20Klb & 2t-5t: NTEP 1:6 000 Class III, S; NTEP 1:10 000 Class III, M 563YS30, 500lb-2.5Klb: NTEP 1:5 000 Class III, S; NTEP 1:9 500 Class III, M 4Klb-20Klb: NTEP 1:6 000 Class III, S; NTEP 1:10 000 Class III, M 563YS, 2Klb-5Klb & 500kg-2t: OIML MAA C5, Y=26 000; 10Klb-20Klb & 3t-10t: OIML MAA C6, Y=8 500; 563YS30, 2Klb-5Klb: OIML MAA C4, Y=15 000; 10Klb-20Klb: OIML MAA C6, Y=8 500; For further available P/N's & specifications per NTEP/OIML classes, please contact us.	

INTERCHANGEABLE REFERENCE			
Brand	563YS		563YS30
Artech			SS30310
Coti Global	CG-23-SSW-02		CG-23-SSW-03
HBM			B35* / H35**
Mettler-Toledo			0793
Rice Lake	RL32019S-HE / RL32218S-HE / RL35082 / RLHTO		RL32018S* / RL32018S-HE / RL35023S* / RL35083 / RL39123
Vishay Celtron			SQB-HSS
Vishay Revere Transducers			9123
Vishay Sensortronics	65083S		65023S* / 65023SS** / 65083
Vishay Tedeia-Huntleigh	3510-kg		3510-lbs

* Environmentally sealed / **Welded seal / ***Environmentally sealed for capacities 1Klb-10Klb
www.anyload.com

Product Datasheet Disclaimer

Information Changes:

All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

 **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.